

4
PATENT
0104-0353P

IN THE U.S. PATENT AND TRADEMARK OFFICE

Applicant: William HOLM et al. Conf.: 8194
Appl. No.: 09/902,110 Group: 2878
Filed: July 11, 2001 Examiner: UNKNOWN

For:
METHOD AND APPARATUS FOR PROVIDING A
SUBSTRATE WITH VISCOUS MEDIUM



LETTER

Assistant Commissioner for Patents
Washington, DC 20231

September 20, 2001

Sir:

Under the provisions of 35 U.S.C. § 119 and 37 C.F.R. § 1.55(a), the applicant(s) hereby claim(s) the right of priority based on the following application(s):

<u>Country</u>	<u>Application No.</u>	<u>Filed</u>
SWEDEN	0002618-7	July 11, 2000

A certified copy of the above-noted application(s) is(are) attached hereto.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fee required under 37 C.F.R. §§ 1.16 or 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

By Paul C. McKinney
Joe McKinney Muncy, #32,334
for #43,368
P.O. Box 747
Falls Church, VA 22040-0747
(703) 205-8000

KM/PCL/ghh
0104-0353P

Attachment

PRV

PATENT- OCH REGISTRERINGSVERKET

Patentavdelningen

Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

(71) Sökande Mydata Automation AB, Bromma SE
Applicant (s)

(21) Patentansökningsnummer 0002618-7
Patent application number

(86) Ingivningsdatum 2000-07-11
Date of filing

Stockholm, 2001-07-10

För Patent- och registreringsverket
For the Patent- and Registration Office

Kerstin Gerdén
Kerstin Gerdén

Avgift
Fee 170:-

PATENT- OCH
REGISTRERINGSVERKET
SWEDEN

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 666 02 86
08-666 02 86

09/902,110

1081

Brick, Stewart et al.
(703) 205-8090

Att. doc. 104-353P

AWAPATENT AB

Kontor/Handläggare

Stockholm/Thomas Skagersten/GAL

MYDATA AUTOMATION AB

Ansökningsnr

Vår referens

SE-2008001

1

METHOD, APPARATUS AND USETechnical field of the invention

The present invention generally relates to the field of providing substrates with viscous medium. More specifically, the invention relates to a method of providing
5 a substrate with viscous medium, a corresponding apparatus, an apparatus for correcting application errors in connection with the application of viscous medium on a substrate, and use of jetting means for said correcting.

10 Background of the invention

In the field of electronics production, it is well known that possible sources of errors are the electronic circuit boards. Mainly, these errors originate from the application of viscous medium, e.g. solder paste, prior
15 to the mounting of components on the board. Over the years, a number of different techniques have been proposed for detecting errors resulting from solder paste application. Originally, this detection was performed manually. Lately, however, the use of cameras in combination with image processing have become the preferred
20 choice for detecting said errors. An example of this can be found in the Swedish Patent Application 9900124-0, which discloses a method and a device for contactless inspection of objects on a substrate.

25 When errors resulting from the application of solder paste have been detected, and preferably identified, appropriate action must ensue. Traditionally, a board containing errors as a result of the application of solder paste is simply taken out of the process. The removed
30 board can then be discarded or, commonly, cleaned and subsequently reinstated at the beginning of the process. Recently, the results of the solder paste application, i.e. critical parameters thereof, are monitored and er-

rors are identified, and the monitored parameters are fed back so that appropriate measures can be taken. This is common in state-of-the-art screen printing applications.

This feedback can, in the simplest case, be a warning message when a parameter has crossed a certain preset limit. The operator can then decide which actions to take. On the other hand, an advanced system could incorporate artificial intelligence to adjust application parameters such as, in the case of screen printing, squeegee pressure, speed and angle, amount of paste on the stencil, cleaning interval, etc. Thus, critical process parameters can be monitored and adjusted so that the application errors can be reduced. However, the specific board containing the detected errors is dealt with in the traditional manner described above, i.e. the faulty board is removed from the entire process.

When using conventional dispensing, i.e. contact dispensing, as opposed to screen printing for the application of solder paste, dispensing heads with integrated measurement capabilities, for measuring the result of the application of solder paste, are known within the art. The measured parameters can be fed back for process control in order to reduce future errors. Since the integrated measurement capabilities can measure the solder paste application of a single dot, e.g. immediately following the dispensing of said dot, process parameters can be altered for the subsequent dispensing of dots on the same board. Thereby, small errors can be detected and process parameters adjusted so that, in the best case, major errors requiring the board to be removed from the process, can be avoided.

Summary of the invention

Thus, an object of the present invention is to provide a solution to the above-mentioned problems and to provide an improved production efficiency.

This and other objects are achieved according to the present invention by providing apparatus and a method having the features defined in the independent claims. Preferred embodiments are defined in the dependent

5 claims.

In general terms, the invention is based on the insight of the advantageous results that can be obtained by using correction measures in relation to the application of viscous medium on a substrate.

10 According to a first aspect of the invention, there is provided a method of providing a substrate with viscous medium, comprising the steps of applying said viscous medium onto the substrate, inspecting the results of said application, determining errors of the application
15 based on said inspection, and correcting at least some of said errors.

According to a second aspect of the invention there is provided a system or an apparatus for providing a substrate with a viscous medium, comprising application
20 means for applying the viscous medium onto the substrate, inspection means for inspecting the results of said application, processing means for determining application errors based on said inspection, and correction means for
correcting at least some of said errors.

25 According to a third aspect of the invention there is provided an apparatus for correcting application errors in connection with application of a viscous medium on a substrate, said apparatus comprising processing means adapted to receive information of said errors in
30 the application of said viscous medium, and correction means for correcting at least some of said errors based on said information.

According to a fourth aspect of the present invention there is provided the use of jetting means for the
35 correction of application errors in regard to viscous medium provided on a substrate.

For the purposes of this application, it is to be noted that the term "viscous medium" should be interpreted as solder paste, flux, adhesive, conductive adhesive, or any other kind of medium used for fastening components on a substrate, or resistive paste; and that the term "substrate" should be interpreted as a printed circuit board (PCB), a substrate for ball grid arrays (BGA), chip scale packages (CSP), quad flat packages (QFP), and flip-chips or the like. It is also to be noted that the term "jetting" should be interpreted as a non-contact dispensing process that utilises a fluid jet to form and shoot droplets of a viscous medium from a jet nozzle onto a substrate, as compared to a contact dispensing process, such as "fluid wetting", which is the act of the viscous medium leaving the dispense tip, contacting and clinging to the substrate and remaining on the substrate as the dispense tip pulls away.

Preferably, use is made of jetting and/or removing means for the correction of errors resulting from the application of a viscous medium on a substrate. Said correction is performed after the application of said viscous medium, but prior to any soldering thereof. Preferably, said correction is also performed prior to the mounting of components, at the locations on the substrate where correction is required. It must, however, be noted that the correction of said errors can be performed after mounting of components at other locations on the substrate. This is for instance the case when mounting components on both sides of a substrate. Then, correction of errors according to the present application can be performed at one side after components have been mounted and attached to the other side of the substrate.

Thus, the correction of viscous medium applied on a substrate according to the present invention must not be mistaken for the known correction of soldered connections, which is performed late in the component mounting cycle after the mounting of components and hardening of

the viscous medium, i.e. reflow of solder paste, used for mechanically and electrically connecting the component to the substrate. An advantage of correcting errors prior to the mounting of components and hardening of the viscous medium is that it is much cheaper, as compared to making corrections late in the mounting process cycle. This is due to the fact that valuable production capacity is not occupied by a substrate that must be corrected. Further, correction performed prior to the mounting of components is easier and requires less correction steps.

According to the present invention, said application of viscous medium is not intended to be limited to a particular method of applying viscous medium, i.e. application through e.g. screen printing, conventional dispensing, jetting, etc. On the contrary, the present invention is intended to be applicable for the correction of any substrate that is provided with a viscous medium, regardless of how the viscous medium was originally applied.

According to one embodiment of the present invention, following the application of viscous medium on a substrate, the result of said application is inspected. This inspection can be performed after the completion of the application of viscous medium on the entire substrate, or can be performed during said application, e.g. at intermittent intervals or continuously, depending on the application method being used. When applying the viscous medium through screen printing, the inspection is preferably performed when the application is completed. When applying viscous medium through contact dispensing or jetting, the inspection can be performed following the dispensing of viscous medium at each specific site or position, or at certain predetermined intervals.

The inspection not only detects whether a site or position has been provided with viscous medium, but also detects whether the correct amount, i.e. volume, of viscous medium has been applied, whether the position of the applied medium is correct, or within a predetermined

fault range, and has the correct shape and height at a given position. The term "correct" has here the meaning of the measured parameter being within a fault range that is predetermined.

- 5 According to alternative embodiments of the invention, the inspection could involve inspection of the entire substrate, all locations on the substrate where viscous medium is to be applied, or only specific locations on the substrate. The latter would preferably involve inspecting specific locations that are particularly error prone, e.g. locations where components are later to be placed which are particularly sensitive to errors in the applied viscous medium, such as components having leads with a very fine pitch, or components which are difficult to inspect after soldering, such as BGA components.

- 15 According to an embodiment of the invention, following the detection of an error, the characteristics of said detected error are determined and stored. Preferably, the error characteristics are further analysed and evaluated to determine whether the error needs correcting. If so, the proper method of correcting said error is also determined. According to an embodiment, the time needed for performing said correction is estimated and stored.

- 25 According to an embodiment of the invention, the application of viscous medium is performed through screen printing. Following the completion of the screen printing, the result of the screen printing is inspected and any errors are detected, determined, and analysed. The results of said inspection can be fed back to the screen printer for enabling the screen printer to correct or adjust parameters. Following the inspection and determination of errors, correction of the determined errors ensues.

- 35 According to another embodiment of the invention, the application of viscous medium is performed using conventional contact dispensing or jetting. This enables

continuous, on-line inspection of the results of said application. Thus, the application of viscous medium at a single location can be immediately inspected, e.g. dot by dot, and the results can both be fed back for adjustment of dispensing or jetting parameters, or can be immediately transferred to means for correcting any detected errors. According to an alternative embodiment, the inspection is performed following the completion of the application of viscous medium on the entire substrate.

Then, and as described above, the inspection could involve inspecting the entire substrate, all locations on the substrate where viscous medium is to be applied, or predetermined specific locations on the substrate.

According to the present invention, the correction of determined errors on a substrate is performed by the use of jetting for applying additional viscous medium. Not only will jetting additional viscous medium onto the substrate overcome the shortcomings of the conventional dispensing as discussed above, jetting is also faster, more accurate, and more flexible in comparison to screen printing as well as conventional dispensing. The use of conventional dispensing often provide a bottle neck that increases the cycle time in the overall component mounting process, as compared to the use of jetting. It has also been found that it is possible to achieve smaller dots when using jetting than when using conventional dispensing. Further, by using jetting, it is possible to apply dots of viscous medium having differing heights, which is hardly possible when using screen printing.

However, at positions where it has been determined that there has been applied too much viscous medium, the surplus viscous medium must be removed. This is performed according to an embodiment of the invention by the provision of removing means capable of removing viscous medium from a specific location on the board. Said removal is preferably performed through suction of the viscous medium. Due to the characteristics of the viscous medium,

e.g. solder paste, the remains on the substrate of viscous medium at a location at which removal of the viscous medium has been performed is generally minute. But, there may be some flux remains left at said locations. However, this is not a problem due to the fact that where cleaning of the substrate is performed following the soldering of components, in order to get rid of deleterious flux that is used when mounting the components, said flux remains will be removed during said cleaning; and in cases where it is not necessary to remove flux following said soldering, the flux remains will not be a problem. Thus, additional cleaning of the substrate following the removal of surplus viscous medium will not be necessary.

The combination of jetting means and removing means for correcting errors on a substrate provided with viscous medium enables correction of all types of application errors. These errors may for instance include applying a surplus of or insufficient viscous medium or insufficient at a given position, applying viscous medium at wrong positions, applying viscous medium where the result of the application is misaligned, applying viscous medium having characteristics deficiencies of some sort, etc.

According to an embodiment of the present invention, the correction of errors is performed in a separate machine, i.e. the substrate is forwarded to the correction machine following the determination that correction of the result of viscous medium application is required. According to an alternative embodiment, the correction machine also comprises the inspection means described above. Then, all substrates are forwarded to the correction machine for inspection and possible correction of detected errors. Preferably, the results of said inspection are fed back to the machine for allowing adjustment of application parameters.

Said embodiment of having a stand alone correction machine is particularly useful when the initial application of viscous medium is performed by screen printing or

contact dispensing. Then, the advantages relating to screen printing and contact dispensing, as recognised by the man skilled in the art and not further described herein, can be combined with the above described advantages of correction of errors through jetting.

According to an alternative embodiment of the invention, the correction means, i.e. jetting means for correction and removing means, are integrated in the machine for performing the initial application of viscous medium onto the substrate. Thus, the inspection can be performed continuously and any correction of the substrate necessary can be done instantly.

Said embodiment of having an integrated machine for both the initial application of viscous medium and the ensuing inspection and correction is particularly useful when the initial application of viscous medium is performed by jetting. Thus, a single jetting means can be utilised for both the initial application and the correction. This would facilitate the construction of the machine and minimise the size of the machine and also would provide a small footprint, i.e. the overall floor space required for the machine. Alternatively, the correction is performed by a separate jetting means not used for the initial application of viscous medium. This would decrease the overall time required for the application and the possible correction.

Generally, a separate machine for the correction, and possibly also for the inspection, would increase line length but decrease the overall cycle time for each substrate as compared to an integrated machine as described above incorporating both the initial application of viscous medium and the subsequent or concurrent correction. Further, an integrated machine where the initial application is performed through screen printing or contact dispensing would have to overcome a number of constructional difficulties.

According to a specific embodiment of the present invention, all errors occurring on a single substrate following the completion of the application of viscous medium, e.g. following screen printing, are jointly analysed and the total amount of corrections needed for the entire substrate is then determined. Thus, it can be determined whether the sum of errors are so great that correction of the errors on the substrate are not worthwhile. Preferably, it has been determined the time required for error correction of each detected error requiring correction, then the overall correction time for the entire substrate is evaluated. If it is found that correction of the errors on the substrate is not worthwhile, the substrate can be removed from the process and cleaned without any corrections being made.

Thus, the use of jetting for correcting errors resulting from the application of viscous medium onto a substrate enables not only error prevention, which is known through the feedback of inspection results, but also error correction. This guarantees that a low defect level can be maintained, which in turn results in the main source of failures in the electronics production is overcome, reducing the production costs considerably. This is done without more than a fractional addition of time required for the overall application of viscous medium on a substrate.

The above mentioned and other aspects, advantages, and features of the invention will be more fully understood from the following description of exemplifying embodiments thereof.

Brief description of the drawings

Exemplifying embodiments of the invention will be described below with reference to the accompanying drawings, in which:

Fig. 1 is a block diagram illustrating a typical prior art arrangement for handling errors resulting from application of viscous medium.

Figs 2-5 are block diagrams illustrating arrangements according to alternative embodiments of the present invention.

Figs 6-11 are flow charts illustrating alternative embodiments of the method according to the present invention.

10

Detailed description of preferred embodiments

In the block diagrams of Figs 1-5, the thick-lined arrows depict the movement of a substrate through the production line. The dashed boxes simply indicate that the means or apparatus depicted within the box can be incorporated in a single machine.

With reference to Figs 2-11, there is illustrated exemplary embodiments of the present invention. As to the means used for applying solder paste, inspecting the results of said application, removing solder paste, and component mounting, use can be made of means which by themselves are known within the art, and the constructional features of which are also known. Therefore, a constructional and functional description of each separate means has been omitted.

With reference to Fig. 1 there is shown a typical prior art arrangement for handling errors resulting from solder paste application. The solid arrows depict the transportation of a substrate through the arrangement. The substrate is first brought to a machine 2 for application of the solder paste. Following the application of solder paste, the substrate is brought to an inspection means 3 where the result of the application is inspected. When the application is performed through contact dispensing or jetting, the inspection could take place simultaneously with the application. Then, of course, the application means 2 and the inspection means 3 are incor-

porated in a single machine 1. If the inspection shows that the result of the solder paste application is satisfactory, then the substrate is conveyed to a component mounting machine 5. If not, then the substrate is taken out of the production line, either discarded cleaned in a cleaning machine 4 and reinstated in the production line prior to the application machine 2.

There will now be described with reference to Figs 1 and 6, a first embodiment of the present invention for correcting errors resulting from solder paste application. A substrate is first brought to an application and inspection machine 10, incorporating both application means 12 and inspection means 14. A conventional method of application is used and therefore not further described. As can be seen from the flow chart in Fig. 6, solder paste is applied to the substrate at 102. Then the inspection of the application result commences at 104 by indicating the starting point for the inspection. The solder paste application is inspected for a position N at 106. At 108, it is determined whether an error is detected for position N and, if so, the parameters of the detected error, e.g. size of solder paste dot, dot position, dot shape, etc., is recorded and, possibly, also fed back to the application means at 109. At 110, there is a check whether all positions to be inspected have been inspected. If not, the position parameter N is incremented and the next position is inspected at 106.

Following the inspection for all selected positions, the parameters are evaluated at 112 to determine whether correction of the substrate is required. If not, the substrate is transferred at 113 to a component mounting machine 18. However, if correction is required, then the total amount of correction needed is calculated at 114. The result of this calculation is defined as a correction value, which at 116 is compared to a threshold value for determining whether correction of the substrate is worthwhile. That is, if there are vast correction actions re-

quired, then it might be more economical to simply discard the substrate. This is of course dependent on the type of substrate and the cost involved for the substrate. If correction is deemed worthwhile, then the substrate is transferred at 118 to a correction machine 16. The correction machine 16 incorporates both means for removing surplus solder paste, as well as jetting means for jetting additional solder paste onto the substrate.

As is understood by the man skilled in the art, the above-mentioned steps of recording, evaluating, determining and sending and retrieving information can be performed by the use of conventional processing means (not shown).

Turning now to figs 3 and 7, there is illustrated a second exemplary embodiment of the present invention. The invention according to this embodiment differs from the first embodiment in that the application means 22 is not incorporated with the inspection means 24. Instead, the inspection means 24 can be incorporated with correction means 26 in a combined inspection and correction machine 20. As is shown in the flow chart of Fig. 7, in this exemplary method 200 the substrate is transferred to the application means 22 at 202 and provided with solder paste. Then, the substrate is at 204 transferred to the inspection and correction machine 20. The inspection means 24 inspects at 208 the solder paste application result for position N.

At 210 it is determined whether the inspection for position N reveals that an error that require correction is detected. If so, the error is corrected by the correction means 26 at step 211. At 212 it is checked whether all positions have been inspected. If so, the substrate is transferred at 214 to the component mounting machine 18. For ease of description, it is indicated in Fig. 7 that the correction for position N is performed directly following the inspection for position N.

However, the inspection means 24 might perform an inspection faster than the correction means 26 can perform the corresponding correction. In reality, the inspection is performed as fast as possible, and the information as to which positions require correction, and which correction that is needed, is continuously transmitted to the correction means 26. Thus, the inspection means 24 does not wait at a specific position for the correction means to finish correcting at that position. This applies equally for the embodiment of Figs 5 and 11, which will follow.

Turning now to Figs 4 and 5, there is shown two alternative embodiments where the initial application of solder paste is performed with jetting means 32, 40. In the embodiment of Fig. 4, there are provided two separate jetting means, one for the initial solder paste application, and one included in the correction means 36 for the correctional jetting of additional solder paste. In the embodiment of Fig. 5, the same jetting means is used for both the initial solder paste application, and for the correctional jetting of additional solder paste. Thus, the application, inspection and correction means are all integrated in one machine 40.

The method 300 for the arrangement illustrated by Figs 4, 8 and 9 differs from the methods of Figs 6 and 7 in that the application for each position can be essentially immediately inspected. Turning to Figs 8 and 9, solder paste is applied through jetting means 32 for position N at step 304. The result of the application is then inspected by the inspection means 34 at step 306. If correction is required, determined at 308, the correction parameters is relayed to the correction means 36 at step 309. The application and inspection then continues at 304 and 306 until solder paste have been applied and the inspection have been performed for all positions, determined at 310. Simultaneously with said application and inspection, the correction means 36 performs correction

of the detected errors at 322 based on information received at 320. After each correction has been completed, a signal indicative thereof is transmitted at step 324 to processing means (not shown). At step 310, it is also determined whether all corrections have been completed before the substrate is transferred to the component placement machine 18 at step 312.

Turning finally to Figs 5, 10 and 11, there are illustrated two alternative methods 400, 500 according to alternative embodiments of the present invention. As described above, a single jetting means is used for both the initial application of solder paste and the subsequent possible corrective jetting of additional solder paste. In Fig. 10 there is shown an alternative where the corrective jetting is performed following the completion of the initial application, whereas in Fig. 11 there is shown an alternative where the jetting correction is performed as soon as an error has been detected. As obvious to the man skilled in the art, any combination of these two alternatives is also possible.

The initial steps 402-410 of method 400 correspond closely to the initial steps 102-110 of method 100, as shown in Fig. 6. However, following the completion of the initial solder paste application and the inspection and recording of errors, correction of the detected errors is performed by the correction means, both where additional jetting is required as well as the removal of solder paste. According to Fig. 10, for ease of illustration, this is performed by resetting the position parameter N, at 412 and looping through all positions on the substrate and correcting them in order, at 414-420. However, any type of correction algorithm can be used. Finally, the substrate is transferred at 422 to the component mounting machine 18.

The method 500 shown in Fig. 11 correspond to the method 300 of Fig. 8 for all steps 502-512, except for step 509. In method 500 the required correction is per-

formed at step 509, whereas at step 309 of the method 300, parameters are transmitted to separate correction means. However, as stated above, the correction for a specific position does not necessarily take place immediately following the inspection of that position.

5 Even though the invention has been described above using exemplifying embodiments thereof, alterations, modifications and combinations thereof, as understood by those skilled in the art, may be made within the scope of the invention, which is defined by the accompanying claims.

10

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

CLAIMS

1. A method of providing a substrate with viscous
5 medium, comprising the steps of
applying said viscous medium onto the substrate,
inspecting the results of said application,
determining errors of the application based on said
inspection, and
10 correcting at least some of said errors.

2. The method as claimed in claim 1, wherein the
step of determining errors comprises the step of evaluat-
ing all of the determined errors and deciding to what ex-
15 tent the determined errors shall be corrected.

3. The method according to claim 1 or 2, wherein the
step of determining errors further comprises the step of
evaluating each of the determined errors and deciding on
20 proper corrective action.

4. The method according to claim 3, wherein the step
of determining errors comprises the steps of
estimating for each of the determined errors the
25 time required for performing said corrective action, and
calculating the overall time required for corrective
action of all determined errors.

5. The method according to any previous claims,
30 wherein said correction comprises jetting of additional
viscous medium onto the substrate and/or removing viscous
medium from the substrate.

6. The method according to claim 5, wherein the step
35 of correcting comprises the step of removing viscous me-
dium from positions on the substrate where viscous medium
has been unintentionally applied.

7. The method according to claim 5 or 6, wherein the step of correcting comprises the step of removing surplus viscous medium from positions on the substrate where more viscous medium has been applied than intended.

8. The method according to any one of claims 5-7, wherein the step of correcting comprises the step of jetting of additional viscous medium to positions on the substrate where no viscous medium has been applied even though intended.

9. The method according to any one of claims 5-8, wherein the step of correcting comprises the step of jetting of additional viscous medium to positions on the substrate where the amount of applied viscous medium is insufficient.

10. The method according to claim 8 or 9, further comprising the steps of inspecting the results of said jetting of additional viscous medium, determining errors of said jetting of additional viscous medium based on said inspection, and correcting at least some of said errors.

11. The method according to any one of the previous claims, wherein the step of applying a viscous medium is performed by jetting.

12. The method according to any one of claims 5-10, wherein the step of applying a viscous medium is performed by jetting and wherein the application of the viscous medium and the jetting of additional viscous medium is performed by the same jetting means.

13. The method according to any one of claims 1-10, wherein the step of applying a viscous medium is performed by screen printing.

5 14. The method according to any one of claims 1-10, wherein the step of applying a viscous medium is performed by contact dispensing.

10 15. The method according to any one of the previous claims, wherein said step of correcting is performed after said step of applying viscous medium has been completed.

15 16. The method according to any one of the previous claims, wherein said step of inspecting is performed after said step of applying viscous medium has been completed.

20 17. The method according to any one of claims 1-14, wherein said step of correcting is performed simultaneously with said step of applying viscous medium.

25 18. The method according to any one of claims 1-15 or 17, wherein said step of inspecting is performed simultaneously with said step of applying viscous medium.

30 19. An apparatus for providing a substrate with a viscous medium, comprising
application means for applying the viscous medium
onto the substrate,
inspection means for inspecting the results of said
application,
processing means for determining application errors
based on said inspection, and
35 correction means for correcting at least some of
said errors.

20. The apparatus according to claim 19, wherein the processing means comprises evaluating means for evaluating each of the determined errors and deciding to what extent the determined errors shall be corrected.

5

21. The apparatus according to claim 19 or 20, wherein said correction means comprises jetting means for jetting of additional viscous medium onto the substrate and/or removing means for removing surplus viscous medium from the substrate.

10

22. The apparatus according to any one of claims 19-21, wherein said application means is a jetting means.

15

23. The apparatus according to any one of claims 19-21, wherein said application means is a jetting means and wherein said application means and said jetting means for jetting of additional viscous medium is the same jetting means.

20

24. The apparatus according to any one of claims 19-21, wherein said application means is a screen printing means.

25

25. The apparatus according to any one of claims 19-21, wherein said application means is a contact dispensing means.

30

26. An apparatus for correcting application errors in connection with application of a viscous medium on a substrate, said apparatus comprising processing means adapted to receive information of said errors in the application of said viscous medium, and

35

correction means for correcting at least some of said errors based on said information.

27. The apparatus according to claim 26, further comprising inspection means for inspecting the results of said application, wherein said processing means receives said information from said inspection means.

5

28. The apparatus according to claim 26 or 27, wherein the processing means comprises evaluating means for evaluating each of the determined errors.

10

29. The apparatus according to any one of claims 26-28, wherein said correction means comprises jetting means for jetting of additional viscous medium onto the substrate and/or removing means for removing surplus viscous medium from the substrate

15

30. Use of jetting means for the correction of application errors in regard to viscous medium provided on a substrate.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

ABSTRACT

- Solder paste application, inspection and correction.
- 5 Following or during application of solder paste on a substrate, the result thereof is inspected and any detected errors are registered. Following an evaluation as to whether correction of these errors is required and if it would be worthwhile, the errors are corrected. The correction involves removing solder paste from locations
- 10 where so required, and jetting of additional solder paste to locations where so required.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2




Fig. 1




Fig. 2

2/7




Fig. 3




Fig. 4




Fig. 5

3/7




Fig. 6

4/7




Fig. 7

5/7




Fig. 8




Fig. 9

6/7




Fig. 10

7/7




Fig. 11